


Ösenlasthaken nach DIN 7541 mit Sicherung, grün lackiert

Art.-Nr.	Nr.	Tragfähigkeit kg	b	d	l	m	s	t	Gewicht je Stück kg
Z3H754105	17	500	18,0	9,0	97,0	18,0	13	71	0,2
Z3H754110	20	1000	25,0	12,5	136,5	25,0	19	100	0,5
Z3H754112	21	1250	28,0	14,0	152,0	28,0	21	112	0,6
Z3H754116	22	1600	31,5	16,0	171,0	31,5	24	125	0,9
Z3H754120	23	2000	35,5	18,0	192,0	35,5	26	140	1,2
Z3H754125	24	2500	40,0	20,0	218,0	40,0	30	160	1,8
Z3H754132	25	3200	45,0	22,4	244,4	45,0	34	180	2,5
Z3H754140	26	4000	50,0	25,0	273,0	50,0	38	200	3,5
Z3H754150	27	5000	56,0	28,0	305,0	56,0	42	224	5,0
Z3H754163	28	6300	63,0	31,5	341,5	63,0	48	250	7,0
Z3H754180	29	8000	71,0	35,5	382,5	71,0	53	280	10,0
Z3H7541100	30	10000	80,0	40,0	430,0	80,0	60	315	14,0



Seil-Gleithaken, rot lackiert

Art.-Nr. ohne Sicherung*	Art.-Nr. mit Sicherung**	Nenngröße in Zoll	Seildurch- messer	Tragfähigkeit in kg	b	d	l	mm o. Sicher.	mm m. Sicher.	Gewicht kg je Stk.
Z3GH13-0	Z3GH13	3/8 - 1/2	9 - 13	1250	70	17	128	25	19	0,7
Z3GH16-0	Z3GH16	5/8	14 - 16	2000	80	22	147	28	22	1,0
Z3GH19-0	Z3GH19	3/4	17 - 19	3000	103	27	174	36	30	1,8
Z3GH26-0	Z3GH26	7/8 - 1	20 - 26	5000	133	33	210	47	40	3,4