




## Kauschen




### Kauschen

DIN 65457, verzinkt (=DIN 6899 Form A)

Art.-Nr.	Nenngröße	Rillenweite (RW)	innere Weite (c)	innere Länge (l)	Rückenstärke (S)	Gewicht per 100
Z3A02	2	2,5	9	20	0,5	0,13
Z3A025	2,5	3	10	21,5	0,5	0,15
Z3A03	3	3,5	11	23,5	0,75	0,21
Z3A035	3,5	4	12	26,5	0,75	0,31
Z3A04	4	5	13	28,5	0,75	0,39
Z3A05	5	6	14	30	1	0,66
Z3A06	6	7	15	33	1	0,84
Z3A07	7	8	16	35	1	1,22
Z3A08	8	9	18	39	1,25	1,88
Z3A09	9	10	20	43	1,25	2,3
Z3A10	10	11	22	47,5	1,5	2,56
Z3A11	11	12	24	51,5	1,5	3,7
Z3A12	12	13	26	56,5	1,75	5,13
Z3A13	13	14	28	61	2	7,21
Z3A15	15	16	32	69,5	2,5	11,03
Z3A16	16	18	35	78	3	16,8
Z3A18	18	20	40	86,5	3,5	24,4
Z3A20	20	22	44	95	4	34,3
Z3A24	24	26	48	100	4	43

### Kauschen

DIN 6899 Form B, verzinkt




Art.-Nr.	Nenngröße	Rillenweite (RW)	innere Weite (c)	innere Länge (l)	Rückenstärke (S)	Gewicht per 100
Z3B03	2,5	3	12	19	1,2	0,5
Z3B04	3,5	4	13	21	1,2	0,8
Z3B05	4	5	14	23	1,7	1
Z3B06	5	6	16	25	2,2	1,6
Z3B07	6	7	18	28	2,2	1,9
Z3B08	7	8	20	32	2,7	3
Z3B10	9	10	24	38	2,9	4,7
Z3B12	11	12	28	45	3,2	6,8
Z3B13	13	13	28	45	3,5	7
Z3B14	13	14	32	51	3,5	10
Z3B16	15	16	36	58	3,8	14,5
Z3B18	16	18	40	64	4,2	19
Z3B20	18	20	45	72	5,2	29
Z3B22	20	22	50	80	5,2	32
Z3B24	22	24	56	90	6,2	50
Z3B26	24	26	62	99	6,5	59
Z3B28	26	28	70	112	7,3	82
Z3B30	28	30	75	120	8	100
Z3B32	30	32	80	128	8	130



## Kauschen

DIN 6899, Form C, verzinkt


Art.-Nr.	Nenngröße	Rillenweite (RW)	innere Weite (c)	innere Länge (l)	Rückenstärke (S)	Gewicht per 100
Z3C11	11	12	27,5	59	6,5	23
Z3C12	12	13	30	64	7	25
Z3C14	14	15	35	75	8	33
Z3C16	16	18	40	86	9,5	48
Z3C18	18	20	45	96	11	106
Z3C20	20	22	50	107	12	145
Z3C22	22	24	55	118	13	169
Z3C24	24	26	60	128	14,5	215
Z3C26	26	28	65	139	15,5	258
Z3C28	28	31	70	150	17	368
Z3C32	32	35	80	171	19	504



## Kauschen

DIN 3090, verzinkt


Art.-Nr.	Nenngröße	Rillenweite (RW)	innere Weite (c)	innere Länge (l)	Rückenstärke (S)	Gewicht per 100
Z309004	4	5	10	20	2,1	1,4
Z309006	6	7	15	30	2,6	3
Z309008	8	9	20	40	4	7,1
Z309010	10	11	25	50	5	17
Z309012	12	13	30	60	6	24
Z309014	14	16	35	70	8	36
Z309016	16	18	40	80	8	50
Z309018	18	20	45	90	9	62
Z309020	20	22	50	100	10	90
Z309022	22	24	55	110	10	100
Z309024	24	26	60	120	10	130
Z309026	26	29	65	130	12	220
Z309028	28	31	70	140	12	140
Z309032	32	35	80	160	15	270



## Vollkauschen

DIN 3091

Art.-Nr.	Nenngröße	Rillenweite (RW)	Bohrung (D1)	äußere Weite (C)	äußere Länge (L)	Gewicht per 100
Z319008	8	9	14 - 20	40	66	18,1
Z319010	10	11	18 - 25	50	82	31,8
Z319012	12	13	21 - 30	60	98	51,5
Z319014	14	16	25 - 35	70	114	79,9
Z319016	16	18	28 - 40	80	130	89,5
Z319018	18	20	31 - 45	90	145	121,1
Z319020	20	22	35 - 50	100	161	161
Z319022	22	24	38 - 55	110	177	211
Z319024	24	26	41 - 60	120	193	271
Z319026	26	29	44 - 65	130	209	355
Z319028	28	31	47 - 70	140	224	420
Z319032	32	35	53 - 80	160	256	630



- Aluminiumkauschen, Nylonkauschen, Rundkauschen, Kauschen mit eingeschweißtem Steg auf Anfragen