



## Schäkel

### Schäkel


handelsüblich gerade, verzinkt



Art.-Nr.	Nenngröße in mm	Nenngröße in Zoll	D1	D2	D3	B1	B2	H	Gewicht per Stück
Z3HÜ316	5	3/16"	5	5	11	10	16	20	0,02
Z3HÜ14	6	1/4"	6	6	14	14	20	25	0,03
Z3HÜ516	8	5/16"	8	8	18	16	24	32	0,07
Z3HÜ38	10	3/8"	10	10	20	24	32	40	0,13
Z3HÜ716	11	7/16"	11	11	22	22	34	46	0,17
Z3HÜ12	12	1/2"	12	12	26	24	38	51	0,24
Z3HÜ916	14	9/16"	14	14	29	29	44	59	0,35
Z3HÜ58	16	5/8"	16	16	33	32	56	69	0,5
Z3HÜ34	19	3/4"	19	19	41	38	66	83	0,8
Z3HÜ78	22	7/8"	22	22	50	44	72	93	1,3
Z3HÜ1	25	1"	25	25	58	45	69	93	2

### Schäkel


handelsüblich geschweißt, verzinkt



Art.-Nr.	Nenngröße in mm	Nenngröße in Zoll	D1	D2	D3	B1	B2	H	Gewicht per Stück
Z3HÜ316G	5	3/16"	5	5	11	10	16	20	0,02
Z3HÜ14G	6	1/4"	6	6	14	14	20	25	0,03
Z3HÜ516G	8	5/16"	8	8	18	16	24	32	0,07
Z3HÜ38	10	3/8"	10	10	20	24	32	40	0,13
Z3HÜ716	11	7/16"	11	11	22	22	34	46	0,17
Z3HÜ12	12	1/2"	12	12	26	24	38	51	0,24
Z3HÜ916	14	9/16"	14	14	29	29	44	59	0,35
Z3HÜ58	16	5/8"	16	16	33	32	56	69	0,5
Z3HÜ34	19	3/4"	19	19	41	38	66	83	0,8
Z3HÜ78	22	7/8"	22	22	50	44	72	93	1,3
Z3HÜ1	25	1"	25	25	58	45	69	93	2

### Schäkel

DIN 82101, Form A, verzinkt



Art.-Nr.	Nenngröße	Tragkraft in Kg	D1	D2	D3	D4	D5	B	H	Gewicht per Stück
Z3A0010	0,10	100	4	5	10	M 5	5	7	15,5	0,02
Z3A0016	0,16	160	5	6	12	M 6	6	8	18	0,02
Z3A0025	0,25	250	7	8	16	M 8	8	11	24	0,05
Z3A0040	0,40	400	8	10	20	M 10	10	14	30	0,09
Z3A0060	0,60	630	10	12	24	M 12	12	17	36	0,17
Z3A010	1,00	1000	13	16	32	M 16	15	21	49	0,36
Z3A016	1,60	1600	17	20	40	M 20	19	27	61	0,75
Z3A020	2,00	2000	19	22	44	M 22	21	30	67	1
Z3A025	2,50	2500	21	24	48	M 24	23	33	73	1,32
Z3A030	3,00	3150	24	27	54	M 27	26	38	83,5	1,85
Z3A040	4,00	4000	27	30	60	M 30	29	42	91	2,5




## Schäkel

DIN 82101, Form A, verzinkt

Fortsetzung

Art.-Nr.	Nenngöße	Tragkraft in Kg	D1	D2	D3	D4	D5	B	H	Gewicht per Stück
Z3A050	5,00	5000	30	36	72	M 36	33	47	111	4
Z3A060	6,00	6300	34	39	78	M 39	37	53	119,5	5,4
Z3A080	8,00	8000	38	45	90	M 45	41	60	139,5	7,9
Z3A100	10,00	10000	42	48	96	M 48	45	66	147	10
Z3A120	12,00	12500	47	52	104	M 52	50	73	158	13,5
Z3A160	16,00	16000	52	60	120	M 60	55	81	185	19,2
Z3A200	20,00	20000	58	68	136	M 68	61	90	211	28
Z3A250	25,00	25000	63	72	144	M 72	67	100	221	34



## Schäkel


DIN 82101, Form C, verzinkt

Art.-Nr.	Nenngöße	Tragkraft in Kg	D1	D2	D3	D4	D5	B	H	Gewicht per Stück
Z3C0040	0,4	400	8	10	20	M 10	10	14	30	0,1
Z3C0060	0,6	630	10	12	24	M 12	12	17	36	0,18
Z3C010	1	1000	13	16	32	M 16	15	21	49	0,39
Z3C016	1,6	1600	17	20	40	M 20	19	27	61	0,8
Z3C020	2	2000	19	22	44	M 22	21	30	67	1,08
Z3C025	2,5	2500	21	24	48	M 24	23	33	73	1,4
Z3C030	3	3150	24	27	54	M 27	26	38	83,5	2
Z3C040	4	4000	27	30	60	M 30	29	42	91	2,7
Z3C050	5	5000	30	36	72	M 36	33	47	111	4,3
Z3C060	6	6300	34	39	78	M 39	37	53	119,5	5,8
Z3C080	8	8000	38	45	90	M 45	41	60	139,5	8,5
Z3C100	10	10000	42	48	96	M 48	45	66	147	10,8
Z3C120	12	12500	47	52	104	M 52	50	73	158	14,4
Z3C160	16	16000	52	60	120	M 60	55	81	185	20,5
Z3C200	20	20000	58	68	136	M 68	61	90	211	29,5
Z3C250	25	25000	63	72	144	M 72	67	100	221	36
Z3C320	32	31500	70	80	160	M 80	74	110	246	49,5
Z3C400	40	40000	79	90	180	M 90	84	125	276	69
Z3C500	50	50000	88	100	200	M 100	93	140	307	93
Z3C630	63	63000	96	110	220	M 110	101	155	339	125
Z3C800	80	80000	110	125	250	M 125	115	175	385,5	180
Z3C1000	100	100000	125	140	280	M 140	130	200	430	260



## Schäkel


hochfest, geschweift, verzinkt



Art.-Nr. mit Augbolzen	Art.-Nr. mit Mutter+Splint	Nenng. in Zoll	Tragkraft in kg	D1	D2	D3	D4 in Zoll	B1	B2	H1	H2	per Stk. Gewicht
Z3HA20050	Z3HB20050	1/4	500	6,5	8	17	5/16	12	20	24	28	0,05
Z3HA20075	Z3HB20075	5/16	750	8	10	21	3/8	13	21	26	31	0,08
Z3HA20100	Z3HB20100	3/8	1000	10	11	25	7/16	16	26	31	36	0,14
Z3HA20150	Z3HB20150	7/16	1500	11	13	27	1/2	18	29	36	42	0,22
Z3HA20200	Z3HB20200	1/2	2000	13	16	30	5/8	21	33	41	48	0,33
Z3HA20325	Z3HB20325	5/8	3250	16	19	40	3/4	27	43	51	60	0,65
Z3HA20475	Z3HB20475	3/4	4750	19	22	48	7/8	32	51	60	71	0,97
Z3HA20650	Z3HB20650	7/8	6500	22	25	54	1	36	58	71	84	1,52
Z3HA20850	Z3HB20850	1	8500	25	29	60	1 1/8	43	68	81	95	2,39
Z3HA20950	Z3HB20950	1 1/8	9500	29	32	67	1 1/4	46	74	90	108	3,15
Z3HA21200	Z3HB21200	1 1/4	12000	32	35	76	1 3/8	52	82	100	119	4,32
Z3HA21350	Z3HB21350	1 3/8	13500	35	38	84	1 1/2	57	92	113	133	5,67
Z3HA21700	Z3HB21700	1 1/2	17000	38	41	92	1 5/8	60	98	124	146	7,79
Z3HA22500	Z3HB22500	1 3/4	25000	44	51	110	2	73	127	146	176	12,51
Z3HA23500	Z3HB23500	2	35000	51	57	127	2 1/4	83	146	171	197	18,5

## Schäkel

hochfest, gerade Augbolzen, verzinkt



Art.-Nr. mit Augbolzen	Art.-Nr. mit Mutter+Splint	Nenng. in Zoll	Tragkraft in kg	D1	D2	D3	D4 in Zoll	B1	B2	H1	H2	Gewicht per Stk.
Z3HA10050	Z3HB10050	1/4	500	6,5	8	17	5/16	12	20	24	28	0,06
Z3HA10075	Z3HB10075	5/16	750	8	10	21	3/8	13	21	26	31	0,08
Z3HA10100	Z3HB10100	3/8	1000	10	11	25	7/16	16	26	31	36	0,13
Z3HA10150	Z3HB10150	7/16	1500	11	13	27	1/2	18	29	36	42	0,19
Z3HA10200	Z3HB10200	1/2	2000	13	16	30	5/8	21	33	41	48	0,31
Z3HA10325	Z3HB10325	5/8	3250	16	19	40	3/4	27	43	51	60	0,55
Z3HA10475	Z3HB10475	3/4	4750	19	22	48	7/8	32	51	60	71	0,96
Z3HA10650	Z3HB10650	7/8	6500	22	25	54	1	36	58	71	84	1,4
Z3HA10850	Z3HB10850	1	8500	25	29	60	1 1/8	43	68	81	95	2,03
Z3HA10950	Z3HB10950	1 1/8	9500	29	32	67	1 1/4	46	74	90	108	2,97
Z3HA11200	Z3HB11200	1 1/4	12000	32	35	76	1 3/8	52	82	100	119	4,01
Z3HA11350	Z3HB11350	1 3/8	13500	35	38	84	1 1/2	57	92	113	133	5,4
Z3HA11700	Z3HB11700	1 1/2	17000	38	41	92	1 5/8	60	98	124	146	7,29
Z3HA12500	Z3HB12500	1 3/4	25000	44	51	110	2	73	127	146	176	11,25
Z3HA13500	Z3HB13500	2	35000	51	57	127	2 1/4	83	146	171	197	16,2